

LIND

FEATURES

- ✓ Low Input Voltage Disconnect
- ✓ High Input Voltage Disconnect
- ✓ Output Over Current Protection
- ✓ Output Short Circuit Protection
- ✓ Internal Over Temperature Protection
- ✓ Automatic Restart 10 seconds after Fault Removal
- ✓ LED Output Power Present Indicator on Adapter
- ✓ LED flash rate identifies fault
- ✓ Reverse polarity disconnect

TECHNICAL SPECS

- ⚡ INPUT VOLTAGE: 11-32 VDC
- ⚡ OUTPUT POWER: 5V @ 3A, 9V @ 3A, 15V @ 3A and 20V @ 5A
- ⚡ RIPPLE/NOISE: 150MV AT 100W LOAD
- ⚡ WEIGHT: 0.683 pounds (0.31 kg) excluding cables
- ⚡ DIMENSIONS: 5.3 x 3.0 x 1.0 inches (135 x 75 x 25 mm) excluding cables
- ⚡ OPERATING TEMP: -20 to +40° C
- ⚡ STORAGE TEMP: -40 to +85° C



FULLY RUGGED 100W POWER ADAPTER

Model #USBC100-5725

TOUGH POWER FOR DEMANDING WORK

Lind's Fully Rugged 100W USB-C power adapter is engineered to power through long shifts and heavy demands without missing a beat. Designed to deliver continuous, reliable power to your mobile devices that use a USB-C input connector for power, it is the only true rugged 100 Watt USB-C power adapter in the market. Built tough, tested to endure, and trusted to perform day after day, it's the adapter that works as hard as the job itself.

The USBC100-5725 is completely sealed with an epoxy material, protecting all critical components from shock, vibration, dust, and water ingress. These features aren't just packed into any power adapter — they're forged into a relentless powerhouse, engineered to take on the toughest conditions, keep your gear running, and never back down, no matter the challenge or environment.

RUGGED ISN'T A FEATURE, IT'S THE STANDARD!

For more information on our isolated adapters or any of our other products, please visit us at www.lindelectronics.com.



(952) 927-6303
(800) 897-8994

14850 Deveau Place
Minnetonka MN 55345



LindElectronics.com

